


2017-03-23 Meeting notes

Date

 23 Mar 2017

Attendees

- Kathleen Carr
- Erich Reiter
- Chris Bond
- Cathy Fowler
- Scott Lewis
- Julia Collins
- Lauren Frederick
- Jon Pals

Goals

- Review previous action items
- Discuss NSIDC questions on mapping spreadsheet
- Discuss  [CMR-2840](#) - JIRA project doesn't exist or you don't have permission to view it.
- Review existing tickets and prioritize
 -  [CMR-3635](#) - JIRA project doesn't exist or you don't have permission to view it.
 -  [CMR-3856](#) - JIRA project doesn't exist or you don't have permission to view it.
 -  [CMR-3849](#) - JIRA project doesn't exist or you don't have permission to view it.
 -  [CMR-3850](#) - JIRA project doesn't exist or you don't have permission to view it.
 -  [CMR-3729](#) - JIRA project doesn't exist or you don't have permission to view it.
- Continue discussion of documentation
 -  [CMR-3353](#) - JIRA project doesn't exist or you don't have permission to view it.
 - Validation
 - Translation

Discussion Items

Item	Notes
Rows 48-52 kind of confused me, although I think 53-56 help clear it up (and make me wonder if 48-52 are just redundant?) Row 57 also seems redundant, and I'm not sure how they relate to rows 58-63 (I think the latter may be a separate "thing").	Rows 48-52 are su Rows 53-56 are de Spreadsheet is wri
<p>I noticed that while the ISO MENDS column for rows 53-56 talks about where the various ISO stuff goes to be read properly, the ROLE is the most important part. I discovered, for instance, that if you put a contact at:</p> <pre>/gmi:MI_Metadata/gmd:distributionInfo/gmd:MD_Distribution/gmd:distributor/gmd:MD_Distributor/gmd:distributorContact/=></pre> <p>but specify the CI_RoleCode as "custodian", it will still read it and process it as an ARCHIVER, even though the Archiver row (55) doesn't list that as a place to look for Archiver.</p>	

<p>The spreadsheet seems to indicate that it will first try to find all but the originator role at:</p> <p>/gmi:MI_Metadata/gmd:identificationInfo/gmd:MD_DataIdentification/gmd:pointOfContact/gmd:CI_ResponsibleParty/</p>	<p>CMR will read Orig /gmi:MI_Metadata/</p>
<p>Then it says "Read if XYZ role didn't exist in #1 above"; however, if you include the data center in both that place and the "read if didn't exist" place, it will actually read from BOTH places (when I pull a DIF record, for instance, after ingest, it had two entries for ARCHIVER, one pulled from each place specified).</p>	<p>CMR will change t</p>
<p>In my tests, the DIF record doesn't show the role associated with the various Data_Center entries.</p>	<p>DIF 9 roles don't e DIF 10 does assign</p>
<p>The contact person associated with the various data centers doesn't seem to be read in; in the DIF, DIF10, and UMM pulls I did after ingesting, it leaves them as being "none".</p>	<p>Erich will look at th</p>
<p>Is it ok to have multiple archivers, multiple distributors?</p>	<p>ECHO can only ha NSIDC may want t to ECHO is straigh This may be more Currently, when CI and first processor</p>

Action items

- ☒ NSIDC to check code for Revision Date in ISO (related to CMR-2840)
- ☐ [Erich Reiter](#) Test combinations of Data Centers and Data Contacts to see if tickets need to be written
- ☐ All new tickets that come from this working group should have label of NSIDC [Erich Reiter](#)
- ☒ Check how CMR maps multiple archivers to a single ECHO archiver? Lauren Frederick
- ☒ Schedule a meeting for next week; we will cancel if not needed Kathleen Carr